

Indoor Lone Worker Alarms Solution

The TWIG Beacon Ex system is designed to locate distressed or injured persons in explosive hazardous areas where GPS is not reliable and other methods do not provide needed accuracy.

TWIG personal alarm devices are located within a microcell network of RF transmitters, laid out to meet position accuracy requirements.

Instantly operational TWIG Beacon locating devices provide years of operating time with their integrated large-capacity battery. Over-the-air configuration facility makes setting up the system easy.

IP67 waterproof housing allows installation in demanding environments.

TWIG personal safety alarm devices report to alarm receiving centre (ARC) TWIG Beacon location information along with last known GPS position, creating a complementary location system for indoor premises capable of global roaming outdoors.



Lone worker protection

Duty of care requires employers to give lone workers means to alert help. Depending on risk assessment, a dedicated alarm device may be required.


- Automatic ManDown function can trigger alert if user is incapacitated.
- When entering a risky situation, request enhanced monitoring with AmberAlert.

Attendance monitoring

Register attendance by swiping TWIG Tag RF Identifiers.

Asset security

Protect vehicles, machinery, caravans and other mobile assets through motion watch and inclusion zones based on TWIG Beacon or GPS.



Alarms monitoring and tracking

TWIG Integrator Kit resources enable integrating TWIG devices with alarm receiving centre.

Optionally the TWIG WebFinder SP software provides a turn-key solution for testing or deployment.

Or receive alarms and reports on your smartphone as SMS with [web link](#), opening up Google Maps view.



II 2 G Ex ib IIC T4 Gb

Twig Com Ltd.

Meriniitynkatu 11
FIN – 24100 SALO
FINLAND

Tel: +358 40 510 5058

Fax: +358 42 510 5058

sales@twigcom.com

www.twigcom.com

Short-range RF beacons

- Location determined using Beacon signals
- Complement GPS location indoors

Small, easy and affordable

- Discreet design
- Instantly operational
- Wireless configuration
- Scalable coverage up to 2000 m² per beacon**
- Add beacons for increased resolution
- No location server system required

Compatibility and communication

TWIG Beacon Ex works with TWIG personal alarm devices equipped with the TWIG short range devices (SRD) Transceiver –option.

- Beacon data is transmitted from TWIG device to ARC in MPTP (Mobile Phone Telematics Protocol) messages, over SMS or GPRS.

Provisioning and security

- Wireless configuration

TWIG Beacon Configuration Adapter

TWIG Beacon Configurator -PC application

- Configuration security

Brief technical specification

- Dimensions: 125 mm x 75 mm x 60 mm
- Weight: 305 g with battery
- Operating temperature -20° C..+40° C
- Power supply alternatives:

Lithium primary battery 19 Ah

- Operating time: 4 years*** (typical, with lithium primary battery)
- Operating frequency: 869,675 MHz
- Transmitting cycle: 4-99 s (adjustable)
- Transmitting power level: -30 dBm - +5 dBm
- Frequency deviation: +/- 5 kHz

Mechanics

- Waterproof (IP67)

ARC integration alternatives

- Display beacon name
- Beacons reference list at ARC

Sales package content

- TWIG Beacon
- Integrated lithium primary battery 19 Ah
- Printed quick installation & configuration guide

ATEX -approved

- II 2 G Ex ib IIC T4 Gb
- Zone 1 Category II Gas intrinsically safe temperature class 4



Options and accessories

- Wireless Configuration Adapter + USB cable



Product images are indicative only, actual product details may differ. Twig Com reserves right to change all information without prior notice. *Some product versions only. **Beacon range varies substantially depending on building structures etc ***Operating times may vary substantially depending on environment and the adopted configuration. ****Charging only above 0° C and below 40° C. TWIG is a registered trade mark of Twig Com Ltd. More information: www.twigcom.com